

# INTERNET CM Modem



Installation Guide

***Don't forget to contact us  
to complete your upgrade!***

877.290.0560

[arvig.net/selfinstall](https://arvig.net/selfinstall)

 **arvig**<sup>®</sup>  
It's All Here

Based on Arvig service area; some restrictions apply. ©Arvig 2023 Item220

## Components required:



cable modem



power cord



modem attenuator pad  
(MAP) *if applicable*\*



Ethernet cable  
(color may vary)



coax cable

**Step 1:** Remove the new modem from the box and place it flat on a desk or table.

**Step 2:** Remove the clear plastic covers from the device—do not block vents.

**Step 3:** Unscrew the coax cable and MAP\* from the old modem and screw them both onto the coax cable port on the new modem. Important: you must connect the MAP\* first. Securely tighten connections—do not overtighten.



**Step 4:** Use the provided power cord to connect the power socket to an appropriate power source. Look at the lights on the front panel; once the @ symbol light is solid (about 5 minutes), proceed with step 5.



**Step 5:** Unplug the Ethernet cable from the old modem and plug it into Ethernet port 1 on the new modem.



**Step 6:** Complete our online form at [arvig.net/selfinstall](https://arvig.net/selfinstall) to complete the setup process. Or, call Arvig Technical Support at 877.290.0560 for assistance. We're also available via online chat at [arvig.net](https://arvig.net).

**Verify your new internet speed by testing it at [speedtest.arvig.com](https://speedtest.arvig.com).**